

SAFETY DATA SHEET

Resilient – Silicone

1. Identification

Product identifier	B9R-RSL-SIL	
Other means of identification		
Product code	B9R-RSL-SIL	
Recommended use	Photopolymerizable ink	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name Address	B9Creations 2828 Plant Street, Ste.2 Rapid City, SD 57702 United States	
Telephone	Phone	+1-605-716-3200
Website E-mail Emergency phone number	www.b9c.com info@b9c.com 3E Company Online	(866) 519-4752
		Number: 334262: (Available 24 hours a day. ay not be available for the Emergency Service.)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
OSHA defined hazards	Not classified.	
Label elements		



▼ ▼
Warning
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging fertility or the unborn child.
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use Dry chemical, CO2, water spray or regular foam. for extinction.
Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

99.92% of the mixture consists of component(s) of unknown acute oral toxicity. 99.92% of the mixture consists of component(s) of unknown acute dermal toxicity. 98.12% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%		
TRADE SECRET*		Proprietary*	20 - < 30		
2-Propenoic acid, 2-methyl-, 2-ethyl-2-[[(2-methyl-1-oxo-2-pr nyl)oxy]methyl]-1,3-propanediyl ester		3290-92-4	3 - < 5		
TRADE SECRET*		Proprietary*	1 - < 3		
Acrylic Acid		79-10-7	< 0.1		
Carbon Black		1333-86-4	< 0.1		
Other components below repor	table levels		60 - < 70		
Impurities					
Chemical name	Common name and synonyms	CAS number	%		
Toluene		108-88-3			
*Designates that a specific chemic	cal identity and/or percentage of composition ha	as been withheld as a trade se	cret.		
Composition comments	Occupational Exposure Limits for impurities a	are listed in Section 8.			
4. First-aid measures					
Inhalation	Remove victim to fresh air and keep at rest in center or doctor/physician if you feel unwell.	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.			
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.				
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.				
Ingestion	Rinse mouth. Get medical attention if symptoms occur.				
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.				
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.				
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor ir attendance. Wash contaminated clothing before reuse.				
5. Fire-fighting measures					
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carb	oon dioxide (CO2).			
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.				
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.				
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full p	protective clothing must be wor	n in case of fire.		
Fire fighting equipment/instructions	Move containers from fire area if you can do	so without risk.			
Specific methods	Use standard firefighting procedures and con	sider the hazards of other inve	olved materials.		
General fire hazards	No unusual fire or explosion hazards noted.				

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
US. OSHA Table Z-2 (29 CFR 1910	.1000)		
Impurities	Туре	Value	
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	Form
Acrylic Acid (CAS 79-10-7)	TWA	2 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Impurities	Туре	Value	
Toluene (CAS 108-88-3)	TWA	20 ppm	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Acrylic Acid (CAS 79-10-7)	TWA	6 mg/m3	
		2 ppm	
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Impurities	Туре	Value	
Toluene (CAS 108-88-3)	STEL	560 mg/m3	
		150 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Impurities	Тур	e	Va	lue
	TW	A	37	5 mg/m3
			100	0 ppm
US. Workplace Environm Components	ental Exposure Level Typ		Va	lue
2-Propenoic acid, 2-methyl-, 2-ethyl-2-[[(2-methyl-1-oxo 2-propenyl)oxy]methyl]-1,3 propanediyl ester (CAS 3290-92-4)		Ą	1 n	ng/m3
blogical limit values				
ACGIH Biological Exposi	ure Indices			
Impurities	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
* - For sampling details, ple	ease see the source do	cument.		
posure guidelines				
US - California OELs: Ski	n designation			
Acrylic Acid (CAS 79- Toluene (CAS 108-88 US - Minnesota Haz Subs	-3) :: Skin designation ap	Can b plies	e absorbed throu e absorbed throu	gh the skin.
Toluene (CAS 108-88 US - Tennessee OELs: S	kin designation		esignation applie	
Acrylic Acid (CAS 79- US ACGIH Threshold Lin			e absorbed throu	gh the skin.
Acrylic Acid (CAS 79- US NIOSH Pocket Guide	to Chemical Hazards:	Skin designation	e absorbed throu	-
Acrylic Acid (CAS 79- US WEEL Guides: Skin d	esignation		e absorbed throu	-
2-Propenoic acid, 2-m 2-ethyl-2-[[(2-methyl-1 opanediyl ester (CAS	-oxo-2-propenyl)oxy]me		e absorbed throu	gh the skin.
propriate engineering ntrols	should be matched or other engineerir exposure limits ha	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
lividual protection measur Eye/face protection		protective equipments of the second s		
Skin protection				
Hand protection	protective gloves (appropriate glove different from one other hazards pres	EN 374) with a prote does not only deper producer to the othe	ective index 6 (>4 nd on its material er. Glove selectio the liquid may pe	d. Select suitable chemical resistant #80min permeation time). The choice of a but also on other quality features and is n must take into account any solvents ar netrate the gloves. Frequent change is y.
Other	Wear appropriate	chemical resistant c	lothing.	
Respiratory protection	In case of insufficion	ent ventilation, wear	suitable respirate	ory equipment.
Thermal hazards	Wear appropriate	thermal protective c	lothing, when neo	cessary.
neral hygiene nsiderations	measures, such as smoking. Routine	s washing after hand	dling the material g and protective	s observe good personal hygiene and before eating, drinking, and/or equipment to remove contaminants. of the workplace

9. Physical and chemical properties

9. Physical and chemical p	properties
Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	slightly acrylic
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	297.65 °F (147.58 °C) estimated
Flash point	> 203.0 °F (> 95.0 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	3481 cP
Viscosity temperature	77 °F (25 °C)
Other information	
Density	1.03 g/cm3
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	1.026
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and tra
Chambred stability	Material is stable under normal conditions

Reactivity	I he product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Information on likely routes of	•			
Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.			
Skin contact	Causes skin irritation. May cause an allergic skin reaction.			
Eye contact	Causes serious eye irritation.	Causes serious eye irritation.		
Ingestion	Expected to be a low ingestion hazard.			
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.			
Information on toxicological eff	iects			
Acute toxicity	Not known.			
Components	Species	Test Results		
Acrylic Acid (CAS 79-10-7)				
<u>Acute</u>				
Inhalation				
LC50	Rat	1200 mg/l, 4 Hours		
Oral				
LD50	Rat	33.5 mg/kg		
Carbon Black (CAS 1333-86-4)				
<u>Acute</u>				
Oral				
LD50	Rat	> 8000 mg/kg		
Impurities	Species	Test Results		
Toluene (CAS 108-88-3)				
Acute				
Dermal				
LD50	Rabbit	12120 mg/kg		
Oral				
LD50	Rat	2.6 g/kg		
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/eye irritation	Causes serious eye irritation.			
Respiratory or skin sensitizatio	n			
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	May cause an allergic skin rea	action.		
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any components present at greater than 0.1% are		
Carcinogenicity	Not classifiable as to carcinog	jenicity to humans.		
IARC Monographs. Overall	Evaluation of Carcinogenicity			
Acrylic Acid (CAS 79-10 Carbon Black (CAS 133 Toluene (CAS 108-88-3) OSHA Specifically Regulat	3-86-4)	 3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans. 001-1052) 		
Not regulated.				
	ogram (NTP) Report on Carcin	-		
Carbon Black (CAS 133		Known To Be Human Carcinogen.		
Reproductive toxicity	Suspected of damaging fertili	-		
Specific target organ toxicity - single exposure	May cause respiratory irritatio	n.		
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	Not an aspiration hazard.			

Chronic effects

Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

	possibility t		armful or damaging effect on the environment.
Impurities		Species	Test Results
Toluene (CAS 108-88-3)			
Aquatic	5050	Weter flag (Denkrig manne)	
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Persistence and degradability	No data is	available on the degradability of any ing	redients in the mixture.
Bioaccumulative potential			
Partition coefficient n-octa Acrylic Acid	nol / water (lo	g Kow) 0.35	
Mobility in soil	No data av	ailable.	
Other adverse effects			e depletion, photochemical ozone creation ential) are expected from this component.
13. Disposal consideration	ons		
Disposal instructions		reclaim or dispose in sealed containers ontainer in accordance with local/regiona	at licensed waste disposal site. Dispose of al/national/international regulations.
Local disposal regulations	Dispose in	accordance with all applicable regulatio	ns.
Hazardous waste code	The waste disposal co		between the user, the producer and the waste
US RCRA Hazardous Wast			
Toluene (CAS 108-88-3		U220	
Waste from residues / unused products		idues. This material and its container m	npty containers or liners may retain some ust be disposed of in a safe manner (see:
Contaminated packaging			ue, follow label warnings even after container is approved waste handling site for recycling or
14. Transport information	ı		
DOT			
Not regulated as dangerous	goods.		
Not regulated as dangerous IMDG	goods.		
Not regulated as dangerous	goods.		
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not establis	shed.	
General information	IMDG Reg	ulated Marine Pollutant. DOT Regulated	l Marine Pollutant.
15. Regulatory information	n		
US federal regulations		ct is a "Hazardous Chemical" as defined 29 CFR 1910.1200.	by the OSHA Hazard Communication
TSCA Section 12(b) Export	Notification	(40 CFR 707, Subpt. D)	
Not regulated. CERCLA Hazardous Subst	ance List (40	CFR 302.4)	
Acrylic Acid (CAS 79-10 Toluene (CAS 108-88-3		Listed. Listed.	
SARA 304 Emergency rele			
Not regulated. OSHA Specifically Regulat			
Not regulated.			

Not listed.	dous substance		
SARA 311/312 Hazardous chemical	Yes		
Classified hazard categories	Skin corrosion or ir Serious eye damag Respiratory or skin Reproductive toxic Specific target orga	ge or eye irritation sensitization	
SARA 313 (TRI reporting) Not regulated.			
ther federal regulations			
Clean Air Act (CAA) Sectio	n 112 Hazardous Air	Pollutants (HAPs) List	
Acrylic Acid (CAS 79-10 Toluene (CAS 108-88-3))		
	n 112(r) Accidental F	Release Prevention (40 CFR 68.130)	
Not regulated. Safe Drinking Water Act (SDWA)	Not regulated.		
		ist 2, Essential Chemicals (21 CFR 1310.02	(b) and 1310.04(f)(2) and
Toluene (CAS 108-8	88-3)	6594	
Drug Enforcement Adr	ministration (DEA). L	ist 1 & 2 Exempt Chemical Mixtures (21 CF	R 1310.12(c))
Toluene (CAS 108-	2	. 35 %WV	
DEA Exempt Chemical			
Toluene (CAS 108-	88-3)	594	
S state regulations			
California Proposition 65	his product can expos	e you to Carbon Black, which is known to the	State of California to cause
Ca Ca	ancer, and Toluene, w	which is known to the State of California to cau more information go to www.P65Warnings.ca	se birth defects or other
California Proposition	65 - CRT: Listed date	e/Carcinogenic substance	
Carbon Black (CAS California Proposition	,	Listed: February 21, 2003 e/Developmental toxin	
Toluene (CAS 108-8 US. California. Candida subd. (a))		Listed: January 1, 1991 Safer Consumer Products Regulations (Cal	. Code Regs, tit. 22, 69502.3,
Acrylic Acid (CAS 7 Carbon Black (CAS Toluene (CAS 108-4	1333-86-4)		
ternational Inventories			
Country(s) or region Europe	Inventory name European Inventor Substances (EINE	y of Existing Commercial Chemical	On inventory (yes/no)* Yes
United States & Puerto Rico		Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compo	onents of this product co	mply with the inventory requirements administered duct are not listed or exempt from listing on the inv	by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date	04-30-2020
Revision date	04-30-2020
Version #	02
NFPA ratings	Health: 2 Flammability: 0 Instability: 0

The information in the sheet was written based on the best knowledge and experience currently available. Attention: This container will have vapour and/or product residues when emptied. All hazard precautions on label must be observed when handling emptied container. Do not cut or weld container. Do not reuse container.